

ARMY RESEARCH LABORATORY



# Navier-Stokes Computation of Shock Tube Exit Jet for Non-Ideal Blast Simulations

Bernard J. Guidos  
Stephen J. Schraml  
U.S. Army Research Laboratory

Dale K. Ota  
Rockwell International Corporation  
Science Center

ARL-TR-1105

APRIL 1996

Approved for public release; distribution is unlimited.

19960521 003

DTIC QUALITY INSPECTED 1



The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.



# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1996		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE  Navier-Stokes Computation of Shock Tube Exit Jet for Non-Ideal Blast Simulations				5. FUNDING NUMBERS  PR: 1L162618AH80	
6. AUTHOR(S)  Guidos, B. J.; Schraml, S. J.; Ota*, D. K.					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army Research Laboratory Weapons Technology Directorate Aberdeen Proving Ground, MD 21010-5066				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army Research Laboratory Weapons Technology Directorate Aberdeen Proving Ground, MD 21010-5066				10. SPONSORING/MONITORING AGENCY REPORT NUMBER  ARL-TR-1105	
11. SUPPLEMENTARY NOTES  *Rockwell International Corporation Science Center, 1049 Camino Dos Rios, Thousand Oaks, CA 91360					
12a. DISTRIBUTION/AVAILABILITY STATEMENT  Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  A computational fluid dynamics study of the exit jet of the U.S. Army Research Laboratory's 1.68-m diameter shock tube is presented. The shock tube exit jet provides a test environment in which to assess vehicle response to non-ideal blast. In the present study, time-accurate Navier-Stokes solutions are generated to simulate a shock tube exit jet test in which pressure probe measurements were obtained. The computational results are compared to the experimental data, as well as to analytical results and other empirical data. An examination is made of the jet flow field structure, and the computational accuracy and requirements are assessed.					
14. SUBJECT TERMS  computational fluid dynamics      non-ideal blast      shock tube      unsteady flow exit jet                                  nuclear weapons      shock waves      viscous flow				15. NUMBER OF PAGES 50	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified		18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified		19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	
20. LIMITATION OF ABSTRACT					



INTENTIONALLY LEFT BLANK



## ACKNOWLEDGMENTS

The authors gratefully acknowledge the contributions from the following U.S. Army Research Laboratory personnel: Dr. Kevin S. Fansler, for technical review and valuable discussions; Mr. Peter C. Muller, for providing the pressure measurement data and additional background information concerning the M113 tests; Mr. Paul Weinacht, for manuscript review and for providing a copy of the 1-D Riemann solver that had been transferred to the laboratory by Dr. Sukumar Chakravarthy several years ago; Mr. Klaus O. Opalka, for transferring the initial problem setup for the USA code computations; and Mr. Richard C. Angelini, for digitizing the videotape images of the experiment and for co-producing numerical flow visualization video segments that could not be incorporated into the report itself.

This work was supported in part by a grant of high performance computing (HPC) time from the Department of Defense HPC Center, U.S. Army Corps of Engineers Waterways Experiment Station, Vicksburg, Mississippi.



INTENTIONALLY LEFT BLANK



## TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES . . . . .	vii
1. INTRODUCTION . . . . .	1
2. SHOCK TUBE CONFIGURATION AND M113 APC TEST . . . . .	1
3. COMPUTATIONAL MODEL . . . . .	3
4. RESULTS . . . . .	6
4.1 Comparison with Analytical Results and Probe Data . . . . .	6
4.2 Additional Examination of the Computed Jet Structure . . . . .	15
5. CONCLUSION . . . . .	22
6. REFERENCES . . . . .	25
LIST OF SYMBOLS . . . . .	27
DISTRIBUTION LIST . . . . .	29



INTENTIONALLY LEFT BLANK



## LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Video Frame of 1.68-m Shock Tube Exit Jet Experimental Setup . . . . .	2
2. Computational Grid Zones for 1.68-m Shock Tube . . . . .	3
3. Magnified View of Computational Grid at Shock Tube Exit . . . . .	4
4. Approximate In-Tube Flow Field at 153.6 ms After Diaphragm Rupture . . .	7
5. Computed Axis Density Compared to Riemann Solution, $t=153.6$ ms . . .	7
6. Computed Axis Pressure Compared to Riemann Solution, $t=153.6$ ms . .	8
7. Computed Axis Velocity Compared to Riemann Solution, $t=153.6$ ms . .	8
8. Computed Axis Temperature Compared to Riemann Solution, $t=153.6$ ms . .	9
9. Computed and Analytical Boundary Layer Thicknesses, $t=153.6$ ms . . . . .	10
10. Computed and Measured In-Tube Static Overpressure . . . . .	11
11. Computed and Measured Out-of-Tube Gauge Overpressure . . . . .	11
12. Computed Mach Number at Out-of-Tube Gauge Location . . . . .	13
13. Computed Dynamic Pressure at Out-of-Tube Gauge Location . . . . .	14
14. Video Frame of Exit Jet Showing Ring Vortex . . . . .	15
15. Reproduction of Schlieren Photograph of Jet taken from Love et al. (1959) . .	16
16. Computed Mach Contours as Shock Exits Tube . . . . .	17
17. Computed Vorticity Magnitude Contours ( $\omega$ ) as Shock Exits Tube . . . . .	18
18. Computed Pitot Pressure Contours ( $p_p/p_\infty$ ) in 0.2 Increments, $t=648$ ms . . .	20
19. Computed Dynamic Pressure Contours ( $q$ ) in 0.1 Increments, $t=648$ ms . . . .	20
20. Computed Mach Contours in 0.2 Increments, $t=648$ ms . . . . .	20
21. Computed Pressure Contours ( $p/p_\infty$ ) in 0.2 Increments, $t=648$ ms . . . . .	20
22. Video Frame of Exit Jet Engulfing M113 Armored Personnel Carrier . . . . .	21



INTENTIONALLY LEFT BLANK



## 1. INTRODUCTION

Non-ideal blast effects must be considered in the prediction of vehicle response and survivability to tactical nuclear weapon detonations. A non-ideal blast environment can be defined as one in which surface characteristics play a significant role. The environment of particular interest here is created by the presence of a thermal layer adjacent to the ground. The resulting non-ideal blast environment consists of an accelerated flow field that possesses a significantly elevated and sustained dynamic pressure following the initial blast wave. The Blast/Thermal Effects Branch of the Weapons Technology Directorate, U.S. Army Research Laboratory (ARL), is contributing to the development of capabilities to simulate and characterize ideal and non-ideal blast environments (Hisley, 1990; Schraml, 1991; Opalka, 1993; Loucks et al., 1995; Schraml, 1995; Ethridge et al., 1995). These computational and experimental capabilities will give the Army the necessary tools to accurately predict blast environments and to protect personnel and equipment.

As part of the ongoing non-ideal blast program, this report documents a computational fluid dynamics (CFD) study of the exit jet of ARL's 1.68-m diameter shock tube. The shock tube exit jet is being used to assess vehicle response to blast as well as to provide experimental validation for more complex CFD simulations. In the present CFD study, Navier-Stokes solutions are generated to simulate a shock tube exit jet test in which pressure probe measurements were obtained. The major objectives of the study are to (1) numerically simulate the exit jet flow field using a Navier-Stokes technique, (2) compare the computational results to analytical and experimental results, and (3) assess the computational accuracy and requirements.

## 2. SHOCK TUBE CONFIGURATION AND M113 APC TEST

The ARL 1.68-m diameter shock tube is located at the Spesutie Island shock tube facility at Aberdeen Proving Ground. The broad interest is the study of vehicle loading in the shock tube exit jet flow field. The shock tube exit jet can produce a high fidelity simulation of the dynamic flow associated with a thermally precursed nuclear weapon blast wave event. The jet diverges a small amount as a function of distance from the exit plane and develops a very high flow velocity.

Currently, the cross-sectional projected area is too small to adequately test full-scale military equipment; an attachable jet spreader is being developed to address this limitation (Loucks et al., 1996). Then the simulated non-ideal blast can uniformly engulf large military equipment such as wheeled and tracked vehicles. In the interim, both experiment and numerical calculation will provide background information necessary to produce high fidelity simulations of non-ideal blast using the shock tube exit jet.



The experimental data used in this report were gathered during a test conducted by the Blast/Thermal Effects Branch using the M113 armored personnel carrier (APC). Figure 1 is a frame of the video record of the test event showing the experimental setup. The M113 APC was parked perpendicular to the shock tube axis, with the upstream side located approximately 15.4 m from the shock tube exit plane. The approximate height and length of the M113 APC are 1.8 m and 4.9 m, respectively. A pitot probe was mounted on a steel frame and situated 10.64 m from the shock tube exit, 0.194 m below the projected shock tube axis. An in-tube pressure gauge (not shown in the figure) was located flush with the wall in the expansion section, 29.11 m upstream from the exit plane.

The total shock tube length is approximately 186 m, with the driver section length approximately 107 m. The wall thickness at the shock tube exit is approximately 11 mm. At the exit plane, the distance between the ground and the bottom of the shock tube is approximately 1.2 m. At the out-of-tube probe location, the distance between the ground and the projected bottom of the shock tube is approximately 1 m. The initial driver overpressure for this particular firing is 634.3 kPa (6.26 atm). The initial temperature in both the driver and expansion sections is ambient.




Figure 1. Video Frame of 1.68-m Shock Tube Exit Jet Experimental Setup.




### 3. COMPUTATIONAL MODEL

The numerical computations do not include the M113 APC, greatly simplifying the numerical grid construction and problem setup. The inclusion of the M113 APC (or other target vehicles), along with its dynamic response coupled to the CFD model, is a future task.

In the present study, the shock tube flow field is modeled using the unified solution algorithm for real gas in two dimensions (USA-RG2) CFD code, developed at the Rockwell International Science Center (RISC), Thousand Oaks, CA. The USA-RG2 code is used here to solve the axisymmetrical form of the Reynolds-averaged Navier-Stokes equations cast in generalized coordinates and strong conservation law form.

The equations are written in a finite volume formulation, and an implicit, approximately factored solution algorithm is used. The explicit convective terms are constructed using an upwind, total variation diminishing scheme which employs Roe's Riemann solver (Roe, 1981). The nonlinear form of the equations is solved by applying a Newton-iterative technique (Rai & Chakravarthy, 1986), although all solutions generated in this study used one iteration per time step. The viscosity terms are retained in each of the two coordinate directions, and a two-equation  $k-\epsilon$  turbulence model for separated flows (Goldberg & Ota 1990) is used. Perfect gas behavior is assumed. Details of all the numerical aspects are presented or can be traced in reports by Chakravarthy (1986, 1988) and Chakravarthy et al. (1985, 1989).

The multi-zone grid capability of the USA-RG2 code was used for the computations reported here. Figure 2 illustrates the five computational grid zones used to model the flow field in and around the shock tube. Zone 1 is the driver section; Zone 2 is the expansion section; Zone 3 is an external region that abuts against the axis and exit plane; Zone 4 is the far wake region adjacent to the axis; Zone 5 is the region that surrounds the shock tube itself and extends upstream from the exit plane. All zonal boundaries are aligned, that is, zonal boundary points along two adjacent zonal boundaries share the same spatial coordinates.



Note: Drawing not to scale

Figure 2. Computational Grid Zones for 1.68-m Shock Tube.



Figure 3 shows a magnified view of the grid at the shock tube exit. Radial grid point clustering is prescribed above and below the radial location corresponding to the shock tube wall in order to improve the resolution of the wall boundary layer and the free shear layer. Axial grid point clustering is prescribed at the exit plane to resolve the curvature of the shock as it exits the tube as well as the formation of the ring vortex. Additional axial grid point clustering (not shown in the figure) is prescribed at the shock tube base and diaphragm. Figure 3 also shows that the grid zones are defined so that the shock tube wall is modeled as a smooth, zero thickness wall. The numerous in-tube protuberances such as section joint weldings, the internally mounted test table (previously used for testing smaller equipment), and cavities (for cameras and other measurement devices) are ignored.

CFD solutions were generated using two different grids. They differ primarily by their respective number of grid points and spatial resolutions, as shown in Table 1. The initial grid was designed with relatively poor grid resolution. The refined grid was constructed after the initial grid solution was found to compare poorly with the out-of-tube probe data. Though the refined grid contains better resolution than the initial grid in some areas of the flow field domain judged to be critical, it also has less resolution in other areas judged to be less critical.

The downstream outflow boundary of Zone 4 is located approximately 290 m from the shock tube exit plane. The outer boundaries of Zones 3, 4, and 5 are positioned approximately 16 m from the axis. The upstream boundary of Zone 5 is positioned at the




Figure 3. Magnified View of Computational Grid at Shock Tube Exit.



Table 1. Some Defining Parameters for Initial and Refined Grids.

	Initial Grid	Refined Grid
<b>No. of Grid Points (axial × radial)</b>		
Zone 1	201×31	140×65
Zone 2	299×31	280×65
Zone 3	101×100	130×150
Zone 4	31×100	80×150
Zone 5	21×70	80×86
Total number of grid points	30,170	65,680
<b>Axial Spacing (m)</b>		
At Base	0.01	0.1
At Diaphragm	0.01	0.01
At Exit	0.01	0.001
At Out-of-Tube Probe	0.45	0.24
<b>Radial Spacing (m)</b>		
At Axis	0.001	0.034
At Wall	0.001	0.0001

same axial location as the diaphragm. The boundary between Zones 3 and 4 is positioned approximately 25 m from the exit plane for the initial grid and 14 m from the exit plane for the refined grid.

The magnitude of the grid point clustering factor,  $F_l$ , was kept within  $\pm 10\%$  for the refined grid, but was as high as 30% for the initial grid. The clustering factor is defined here as

$$F_l = \frac{\Delta s_{l+1} - \Delta s_l}{\Delta s_l} \times 100\% \quad (1)$$

in which  $\Delta s_l$  and  $\Delta s_{l+1}$  are adjacent grid point spacings between grid indices  $l$  and  $l + 1$  in either of the two computational coordinate directions.

All grid elements except those in Zone 1 are initialized to ambient conditions. The ambient temperature, density, and pressure are assumed to be 288.15 K, 1.225 kg/m<sup>3</sup>, and 101.325 kPa, respectively. The grid elements in Zone 1 are initialized to the driver conditions discussed in the previous section. The diaphragm rupture event is simply modeled as two separately initialized domains in contact with each other. All wall boundaries are modeled as adiabatic. The Zone 4 downstream outflow boundary, the Zone 5 upstream boundary, and the outer boundaries of Zones 3, 4, and 5 all use a zero normal gradient extrapolation boundary condition.



Two CFD solutions were generated using the initial grid. They differed only in the time steps that were prescribed as the solutions progressed. In each case, the time step was determined by prescribing a minimum allowable CFL (Courant-Friedrichs-Lewy) number. For the first solution, the CFL number was prescribed to be 1.0 at the onset of the computation and was increased to 20.0 by the time the shock exited the tube. For the second solution, the CFL number was prescribed to be 0.1 at the onset, increased to 20.0 before shock exit, decreased to 1.0 during shock exit, and increased up to 20.0 thereafter. This second solution was generated because the first solution compared poorly with the out-of-tube pressure probe data. However, the second solution showed no noticeable improvement in the pressure probe comparison. The initial grid results, to be shown in the next section, are those of the second, reduced CFL number, solution.

One CFD solution was generated using the refined grid. For the refined grid solution, the CFL number was prescribed to be 1.0 at the onset of the computation; increased to 20.0 before shock exit; decreased to 0.1 during shock exit; and increased to 20.0 thereafter. The relatively small CFL number of 0.1 used at shock exit was necessary to prevent the numerical solution from computing unreal flow conditions (specifically, negative densities), which led to termination of the computation.

The computations were performed on a Cray Y-MP computer at U.S. Army Corps of Engineers Waterways Experimental Station, Vicksburg, Mississippi, using a single processor. The initial grid solutions used approximately 100 central processing unit (CPU) hours and 2.3 million words of memory each, while the refined grid solution used approximately 200 CPU hours and 3.6 million words of memory. The numerical simulations were made to simulate the first 1600 ms of the event following diaphragm rupture.

## **4. RESULTS**

### **4.1 Comparison with Analytical Results and Probe Data**

Validation of the numerical results begins with an examination of the in-tube flow field before shock exit. A 1-D Riemann solution was generated to compare with the in-tube Navier-Stokes solutions. The Riemann solution, which excludes viscous effects, is an analytical solution valid along the entire length of the shock tube before shock exit. A representative comparison between the Navier-Stokes and Riemann solutions is included here for a time corresponding to 153.6 ms after diaphragm rupture. The in-tube flow field at this time is illustrated in Figure 4. From this view, the shock travels to the right and is within 1 meter from the exit. The contact surface trails the shock and separates the expanded driver air from the air that has been processed by the shock. The expansion waves move to the left.






Figure 4. Approximate In-Tube Flow Field at 153.6 ms After Diaphragm Rupture.

Figures 5 through 8 show the density, pressure, velocity, and temperature from the Riemann solution compared to their respective axis values from the Navier-Stokes solutions at 153.6 ms. In all cases, the flow field properties and structural features compare well between the analytical and numerical solutions. The initial and refined grid Navier-Stokes solutions are plotted as a single curve because they were virtually indistinguishable in these comparisons. The Riemann comparisons serve as standard, preliminary indicators of grid resolution adequacy and solution integrity for the computed axial in-tube flow field before shock exit using both the initial and refined grids.




Figure 5. Computed Axis Density Compared to Riemann Solution,  $t=153.6$  ms.






Figure 6. Computed Axis Pressure Compared to Riemann Solution,  $t=153.6$  ms.




Figure 7. Computed Axis Velocity Compared to Riemann Solution,  $t=153.6$  ms.






Figure 8. Computed Axis Temperature Compared to Riemann Solution,  $t=153.6$  ms.

An examination of the computed shock tube wall boundary layer development before shock exit reveals additional insight into the accuracy of the Navier-Stokes solutions. As expected, the initial grid, with its relatively poor radial grid resolution near the wall, fails to capture the boundary layer throughout the duration of the computation. Specifically, no boundary layer velocity deficit can be discerned farther than one or two grid points from the wall. In this respect, the refined grid provides a substantial improvement in boundary layer resolution, although it does not completely resolve the laminar sublayer.

The boundary layer thickness from the refined grid solution can be compared to an analytical result. The boundary layer edge is assumed to be located where the axial velocity is 99% of the free stream (or, in this case, the axis) value. The boundary layer thickness  $\delta$  is the distance from the wall to the boundary layer edge. An analytical expression for  $\delta$  near a planar shock perpendicular to a flat plate is given by Sedney & Kitchens (1976) as

$$\delta = x_s Re_s^{-1/5} \quad (2)$$

in which

$$Re_s = \frac{\gamma M_s^2 p_\infty x_s}{u_s \mu_\infty} \quad (3)$$

In this expression,  $x_s$  is the distance from the shock;  $M_s$  is the shock Mach number;  $u_s$  is the shock speed; and  $p_\infty$  and  $\mu_\infty$  are the free stream pressure and viscosity, respectively.



Figure 9 shows the comparison of wall boundary layer thickness for the refined grid solution and the 2-D analytical result. The analytical expression, Equation (2), applies only to the region between the contact surface and the shock. The comparison is shown at the same time as the previous Riemann comparisons (153.6 ms), just before shock exit. The maximum computed boundary layer thickness occurs at the contact surface. The analytical solution shows approximately one-third greater boundary layer thickness than the numerical solution. The comparison is considered favorable as a qualitative indicator of solution accuracy, considering the large sensitivity of boundary layer thickness.




Figure 9. Computed and Analytical Boundary Layer Thicknesses,  $t=153.6$  ms.

Figures 10 and 11 show the comparison of computed and measured pressures for the in-tube and out-of-tube probes. Whereas the computed pressure histories are referenced to the time of diaphragm rupture, the original measured pressure histories were referenced to the time at which the measurement equipment began recording. To compare the computed and measured results, the times of the measured data have been shifted so that the initial disturbances are aligned with those of the computed solutions.

Figure 10 shows the comparison of computed static overpressure ( $p - p_\infty$ ) with that of the in-tube probe. Within 650 ms after diaphragm rupture, the computed overpressures from both the initial and refined grid solutions differ from the measured overpressure by at most 10%. Beyond 650 ms, both computed pressure histories decrease more rapidly than the measured history. Near 400 ms, the refined grid solution shows noticeable improvement






Figure 10. Computed and Measured In-Tube Gauge Static Overpressure.




Figure 11. Computed and Measured Out-of-Tube Gauge Overpressure.



over the initial grid solution, capturing the pressure peak in the experimental data. It is inconclusive if the pressure peak is attributable to the presence of the boundary layer, which, as already mentioned, is not resolved by the initial grid. The computed displacement thickness of the in-tube boundary layer was examined and found to be two orders of magnitude less than the computed edge thickness already shown in Figure 9. A quasi-one-dimensional consideration, given the subsonic flow condition within the tube, states that a decrease in effective cross-sectional area will cause an increase in velocity and a decrease in pressure, exactly the opposite effect shown by the data. Instead, the pressure peak may be attributable to the elevated temperature levels within the boundary layer, which cause an increase in pressure, i.e., a thermodynamic effect. The pressure peak may also be an exit plane effect that propagates upstream and is more adequately captured by the improved axial resolution of the refined grid.

Figure 11 shows the comparison of the computed gauge overpressure ( $p_p - p_\infty$ ) with that of the out-of-tube probe. For  $M \leq 1$ , the pitot pressure ( $p_p$ ) is the same as the stagnation pressure; for  $M \geq 1$ , it is the equivalent stagnation pressure behind a normal shock. The pressure measurements from the out-of-tube probe have fluctuations with amplitudes of approximately  $\pm 30$  kPa, much greater than the in-tube probe. The larger fluctuations associated with the out-of-tube probe are likely attributable to vibrations within the steel frame mount. The initial 10-kPa peak occurring at about 190 ms signifies the arrival of the weakened shock and is accurately captured in both computed solutions. The next 100 ms signify a highly transient period in which the measured overpressure abruptly rises to nearly 200 kPa, drops to less than 50 kPa, and recovers to approximately 150 kPa. Both computations capture the initial rise, but neither captures the abrupt drop and recovery. The refined grid solution overpressure, however, at least remains at a level comparable to the measurement at 300 ms.

The computational result does not capture the highly transient pressure probe response between 200 and 300 ms. The experimental results of Loucks et al. (1996) for a scaled model of the 1.68-m shock tube exit jet indicate that ground effects are negligible for several lower pressure cases with no vehicle. (No scaled tests were reported for the higher driver pressure examined here.) It may be argued that the presence of the M113 APC in the actual test may influence the out-of-tube probe measurement. The initial shock, traveling approximately 513 m/s, travels from the probe to the M113 in only 14 ms. The reflected shock travels upstream and interacts with the flow field, reaching the probe at approximately the same time as the first pressure rise to 200 kPa and contributing to the large pressure variations measured during this time period. In this scenario, ground effects could also influence the pressure at the out-of-tube probe. A conclusive determination of the vehicle effect on the measured pitot pressure could be obtained by including a simple axisymmetrical body in the present axisymmetrical flow model and observing the computed pitot pressure response at the probe location.



The largest measured gauge overpressures occur between 400 and 700 ms, at which time, the driver gas reaches the probe. Large differences are apparent between the two computed solutions, with the initial grid solution predicting the gauge overpressure to only within about 50% of the measured values during this time interval. The refined grid solution, on the other hand, predicts the gauge overpressure within the fluctuations of the measured values from 400 to 600 ms.

Figure 11 also shows that the small additional rise in the measured out-of-tube gauge overpressure between 600 and 700 ms is not captured in the refined grid solution. The possibility that the M113 APC is influencing the pressure field at the probe location can be eliminated; Figure 12 shows the computed Mach number at the probe location for the refined grid solution. From 400 to 700 ms, the computed Mach number is approximately 1.44 (i.e., supersonic); therefore, a bow shock can be expected to form upstream from the vehicle. An ideal upper bound estimate of the shock standoff distance ahead of the vehicle can be obtained from the graph shown by Liepmann and Roshko (1957). The actual geometry is more complex than the cases available in the reference. However, assuming the limiting case of a flat nosed axisymmetrical geometry of diameter equal to the length of the M113 APC, the location of the bow shock vertex at Mach 1.44 is found to be approximately 1.5 m downstream from the probe. It is concluded that, during this time period, the pressure measurement is not likely to be influenced by the presence of the vehicle.




Figure 12. Computed Mach Number at Out-of-Tube Gauge Location.



Figure 11 also shows that, beyond 700 ms, the computed pressures decay more slowly than the measured values. The video record of the test shows the steel frame mount to be thrown at least 20 m by the force of the exit jet. The cloud of condensation (and possibly dust) in the video makes it impossible to visually estimate the time at which the steel frame becomes displaced. The poor agreement beyond 700 ms and the negative measured overpressures are possible indicators that the steel mounting frame has been displaced and the measured pressure is no longer valid.

Figure 13 shows the computed dynamic pressure of the initial and refined grid solutions. The dynamic pressure is the most relevant parameter for evaluating the response of bodies to drag forces that cause displacement and/or overturning. The figure shows that the refined grid solution predicts a significantly higher dynamic pressure at the out-of-tube probe location compared to the initial grid solution. The computed dynamic pressure of the refined grid solution reaches sustained magnitudes of 125 to 150 kPa, demonstrating the capacity of the 1.68-m shock tube exit jet to achieve conditions useful for simulating a particular non-ideal nuclear blast environment.




Figure 13. Computed Dynamic Pressure at Out-of-Tube Gauge Location.



## 4.2 Additional Examination of the Computed Jet Structure

The previous discussion demonstrated that the refined grid solution provides a significantly improved flow field prediction compared to the initial grid solution. Visualization of the two flow fields revealed additional differences between the initial and refined grid solutions which, for brevity, are not included here. The discussion made in this section of the computed exit jet flow field structure focuses on the refined grid solution.

Figure 14 shows a frame of the video record of the M113 test at a time when the shock just exited the tube and a ring vortex is the only visible flow structure. The vortex ring is visible in the photograph because the air (specifically, the water vapor) within it has reached temperatures low enough to condense. The low temperatures result from high velocity and low pressure within the vortex core. It is noted that only two frames of the video record show any visible sign of condensation within the ring vortex. The camera speed is 30 frames per second, equivalent to an interval of approximately 33.3 ms between images. It follows that the vortex is visibly condensed for a time duration of between 33.3 and 99.9 ms. It may be assumed that the vortex exists for a longer period of time than is apparent in the video but it is not visible.



Figure 14. Video Frame of Exit Jet Showing Ring Vortex.



Schlieren photographs (Love et al., 1959) and spark shadowgraphs (Schmidt & Lyon, 1988) of underexpanded sonic jets show the air, upon tube exit, to first expand and then recompress through a conical, oblique shock whose vertex is oriented upstream. Depending on the precise exit conditions, the shock vertex may be pointed or it may be capped with a normal shock (also referred to as a Mach disc or Riemann wave). The pattern formed by this initial expansion and recompression is the first in a periodic chain that forms as the jet develops. Such a chain is shown in Figure 15, a reproduced Schlieren photograph from Love et al. (1959), showing an exit jet from a 3.46-mm diameter nozzle having almost identical exit conditions (specifically  $M_j=1.0$  and  $p_j/p_\infty=1.76$ ) as the present study. The chain-like structure, which consists of conically shaped features that appear triangular-like from this side view, decays and loses axisymmetry farther from the exit.



Figure 15. Reproduction of Schlieren Photograph of Jet taken from Love et al. (1959).

Figure 16 shows computed Mach contours from the refined grid solution at 157, 159, 161, and 172 ms after diaphragm exit. The shock exits the tube approximately 155 ms after diaphragm rupture. After exiting the tube, the shock curves around the wall, and by 159 ms, the curvature has propagated to the axis. By 161 ms, the initial expansion emanating from the wall has reached the axis; that is, the air on the axis has begun to expand. The exit flow conditions become nearly sonic. By 172 ms, the initial expansion is fully formed and its downstream edge intersects the axis approximately 3/4 diameter from the exit. The air begins the process of forming a shock that is smeared as it is captured in the computed solution.

Figure 17 shows computed vorticity magnitude contours from the refined grid solution for times of 157, 159, 161, and 172 ms after diaphragm rupture. Of primary interest is the ring vortex, which is computed to reach its largest magnitude immediately upon tube exit. The numerical solution shows the vortex to rapidly move away from the exit and dissipate, separating from the region of vorticity that constitutes the shear layer of the jet. Although not shown in the figure, the numerical solution shows the computed vortex to dissipate






Figure 16. Computed Mach Contours as Shock Exits Tube.






Figure 17. Computed Vorticity Magnitude Contours ( $\omega$ ) as Shock Exits Tube.



almost completely by approximately 75 ms after shock exit, which is qualitatively consistent with the video record. The separate contributions of inviscid and viscous effects were not studied here, but an inviscid computation of the problem using the same grid would quantify the importance of the two effects on the vortex formation and history, as well as on other aspects of the flow field.

Figures 18 through 21 show flow field contours at 648 ms after diaphragm rupture, highlighting the chain-like structure as it is captured within the numerical solution. Figure 18 illustrates that the accuracy of the computed wavelength and spatial decay of the chain-like structure can significantly affect the pitot pressure at the probe location. In contrast, the dynamic pressure contours in Figure 19 show less amplitude variation along the axis near the probe location, demonstrating that the sensitivity of the predicted dynamic pressure (and vehicle response) to the computed wavelength and spatial decay of the chain-like structure are probably minimal.

Figures 20 and 21 show Mach number and static pressure contours, respectively, at 648 ms after diaphragm rupture. At this time, the computed jet is well developed and more steady, compared to other times during the event. A chain-like structure is apparent in both sets of contours. Direct examination of the computed solution data represented by Figures 20 and 21 shows the exit Mach number on the axis to be  $M_j=1.08$  and the exit pressure to be  $p_j/p_\infty=1.79$ . The computed flow structure can be qualitatively compared to the Schlieren photograph of Figure 15. The conical shape of the flow structures is not readily apparent in the contour plots of the computed solution, indicating a possible need for improved grid resolution to more precisely resolve the embedded flow gradients.

The computed primary wavelength of the chain-like structure can be obtained directly from the solution data represented in Figures 18, 20, or 21. The primary wavelength normalized by the tube diameter is denoted  $w/d$ , and the computed value is assumed here to be the distance along the axis from the tube exit to the first maximum pressure location. The computed flow field solution shows this distance to be 1.48 diameters. This value can be compared to the semi-empirical correlation of the primary wavelength given by Love et al. (1959) as

$$w/d = 1.55\sqrt{M_j^2(p_j/p_\infty) - 1} - 0.55\sqrt{M_j^2 - 1} \quad (4)$$

Using the computed exit values given above, Equation (4) yields a value of  $w/d=1.40$ , approximately 6% less than the value in the computed flow field solution.

The graphical correlations of Love et al. (1959) also indicate that, for the exit conditions of the present study, the initial expansion outside the shock tube will focus very close to the axis. At this location, the expansion will culminate as either the vertex of an oblique, conical shock or, at most, a Mach disc of very small diameter.






Figure 18. Computed Pitot Pressure Contours ( $p_p/p_\infty$ ) in 0.2 Increments,  $t=648$  ms.



Figure 19. Computed Dynamic Pressure Contours ( $q$ ) in 0.1 Increments,  $t=648$  ms.




Figure 20. Computed Mach Contours in 0.2 Increments,  $t=648$  ms.




Figure 21. Computed Pressure Contours ( $p/p_\infty$ ) in 0.2 Increments,  $t=648$  ms.



An evaluation can be made of the accuracy of the computed focal length, which is the distance along the axis from the exit plane to the shock vertex or to the Riemann wave. The graphical correlations of focal length given by Love et al. (1959) do not include the exit conditions of the present case. However, using the available condition  $M_j=1.0$  and the computed condition  $p_j/p_\infty=1.79$ , the focal length is graphically shown to be about 0.85 diameter. If, in the computed solution, the focal length is measured from the exit to the downstream location on the axis where the first pressure minimum occurs, the computed focal length is 0.88 diameter, about 3.5% greater than the graphically obtained value.

Finally, Figure 22 shows a video frame of the exit jet impinging and engulfing the M113 APC. The front edge of the M113 is just barely visible, and this video frame represents the final frame in which the vehicle can be seen. Most of the jet is visibly condensed and suggests that the implementation of a jet spreader would allow the vehicle to be completely immersed in the jet.



Figure 22. Video Frame of Exit Jet Engulfing M113 Armored Personnel Carrier.



## 5. CONCLUSION

A CFD study of an exit jet from the ARL 1.68-m diameter shock tube has been presented. The time-dependent Navier-Stokes code USA-RG2, developed at Rockwell International Science Center, was used in axisymmetrical mode to compute the shock tube flow field from the time of diaphragm rupture through the duration of the event (about 1600 ms).

Three CFD solutions were generated, employing two different grids. All three CFD solutions compared well with a Riemann solution for times preceding shock exit. Only the refined grid solution resolved the wall boundary layer enough to compare reasonably well with an analytical solution for boundary layer thickness between the shock and contact surface before shock exit. All three solutions compared reasonably well with the measured in-tube probe pressure history, although the refined grid solution more clearly captured a peak in the data thought to be attributable to boundary layer effects. Only the refined grid solution compared reasonably well with the measured out-of-tube probe pressure history. The dynamic pressure response outside the shock tube, the most relevant parameter for evaluating dynamic vehicle response, was significantly different between the initial and refined grid solutions.

The experimental data were available from a shock tube test conducted on the M113 APC, which was parked downstream from the shock tube exit plane, beyond the out-of-tube pressure probe. This particular firing corresponded to a shock tube case having an initial driver overpressure ( $p/p_\infty$ ) of 6.26, the largest of three shots. The computational model did not include the M113 APC, and some differences in the computed and measured overpressures at the out-of-tube probe location were attributed to the presence of the vehicle influencing the measured pressure history.

Comparison of the computed jet flow structure to video records of the test and to empirical data showed mixed results. The computation captured the brief appearance of the ring vortex that follows initial shock exit, and the computed time duration of the vortex was consistent with the video record. The computation also captured the chain-like structure of expansions and recompressions within the jet, although their conical shapes were not captured precisely enough to reproduce the triangular appearance as illustrated by a Schlieren photograph of a jet with almost identical exit conditions. Comparison of the computed primary wavelength of the chain-like structure with an empirical correlation indicated agreement within 6%. Comparison of the computed focal length of the initial expansion (i.e., the location of the shock vertex or Mach disc) with an empirical, graphical correlation indicated agreement within 3.5%. Improved axial grid resolution in the region downstream from the exit could improve the resolution of the flow structure, although dynamic pressures near the out-of-tube probe location may not be substantially affected.

The refined grid computation was performed using approximately 200 hours of single processor CPU time on a Cray Y-MP computer. Substantial reduction in the required CPU time for this class of problem can be achieved by using parallel processing capabilities that



are becoming available on various computing platforms. Reductions may also be achieved as a result of determining the importance of modeling issues such as viscosity, turbulence, or boundary layer effects, which substantially affect the CPU usage. Additional time savings could have been achieved in the present study by using the USA code capability that allows inactive zones to be carried along without numerical processing – an example of the importance of user expertise as it pertains to computational efficiency.

Overall, the study demonstrates that the CFD model can accurately simulate important aspects of the dynamic flow associated with the shock tube exit jet. The study provides a benchmark of the computational requirements for the problem. The details should contribute to the formulation of CFD simulations that model target vehicle response to non-ideal blast environments.



INTENTIONALLY LEFT BLANK



## 6. REFERENCES

- Chakravarthy, S.R., "The Versatility and Reliability of Euler Solvers Based on High-Accuracy TVD Formulations," AIAA Paper No. 86-0243, 1986.
- Chakravarthy, S.R., "High Resolution Upwind Formulations for the Navier-Stokes Equations," von Karman Institute for Fluid Dynamics, Lecture Series 1988-05, Computational Fluid Dynamics, March 7-11, 1988.
- Chakravarthy, S.R., K.Y. Szema, U.C. Goldberg, and J.J. Gorski, "Application of a New Class of High Accuracy TVD Schemes to the Navier-Stokes Equations," AIAA Paper No. 85-0165, 1985.
- Chakravarthy, S.R., K.Y. Szema, and J.W. Haney, "Unified Nose-to-Tail Computational Method for Hypersonic Vehicle Applications," AIAA Paper No. 89-2564, 1989.
- Ethridge, N.H., J.H. Keefer, J.E. Crepeau, R.G. Ekler, L.W. Kennedy, C.E. Needham, and S.H. Rogers, "Real Surface (Non-Ideal) Effects on Nuclear Explosion Airblast from PRISCILLA-Type Events, Part I: Comparison and Evaluation of Ideal and Non-Ideal Airblast From PRISCILLA Computations; and Part II: SHARC Hydrocode Calculations of the PRISCILLA Event (Phase I)," ARL-CR-277, U.S. Army Research Laboratory, Aberdeen Proving Ground, Maryland, October 1995.
- Goldberg, U.C., and D.K. Ota, "A  $k-\epsilon$  Near Wall Formulation for Separated Flows," AIAA Paper No. 90-1492, 1990.
- Hisley, D.M., "Computational Studies for 1/57-Scale Large Blast Simulator (LBS) Configurations with the BLAST2D Code," BRL-TR-3152, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, September 1990. (AD A227514)
- Liepmann, H.W. and A. Roshko, Elements of Gas Dynamics, Wiley, New York, 1957.
- Loucks, R.B., P.C. Muller, R.L. Thane, T.C. Cline, L.G. Ferguson, and C. Mermagen, "Simulation of Non-Ideal Blast with a Shock Tube Exit Jet," ARL-TR-984, U.S. Army Research Laboratory, Aberdeen Proving Ground, Maryland, February 1996.
- Love, E.S., C.E. Grigsby, L.P. Lee, and M.J. Woodling, "Experimental and Theoretical Studies of Axisymmetric Free Jets," National Aeronautics and Space Administration Technical Report R-6, 1959.
- Opalka, K.O., "Numerical Simulation of the Flow in a 1:57-Scale Axisymmetric Model of a Large Blast Simulator," ARL-TR-111, U.S. Army Research Laboratory, Aberdeen Proving Ground, Maryland, April 1993. (AD A265551)
- Rai, M.M., and Chakravarthy, S., "An Implicit Form for the Osher Upwind Scheme," AIAA Journal, Vol. 24, No. 5, pp. 735-743, 1986.
- Roe, P.L., "Approximate Riemann Solvers, Parameter Vectors, and Difference Schemes," Journal of Computational Physics, Vol. 43, pp. 357-372, 1981.
- Schmidt, E.M., and D.H. Lyon, "Measurement of the Flow from the Open End of a Shock Tube," Proceedings of TTCP Panel W-2, KTA-7 Workshop on the Computation of Weapon Launch Blast Overpressure, BRL-SP-76, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, December 1988. (AD B130619)
- Schraml, S.J., "Performance Predictions for the Large Blast/Thermal Simulator Based on Experimental and Computational Results," BRL-TR-3232, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, May 1991. (AD A235728)



Schraml, S.J., "Exploratory Analysis of Helium Layer Usage for Dynamic Pressure Enhancement in the Large Blast/Thermal Simulator," ARL-TR-869, U.S. Army Research Laboratory, Aberdeen Proving Ground, Maryland, September 1995. (AD A264396)

Sedney, R., and C.W. Kitchens, "Turbulent Boundary Layers in Blast Wave and Shock Tube Flows," BRL-R-1907, U.S. Army Ballistic Research Laboratories, Aberdeen Proving Ground, Maryland, August 1976. (AD A029435)



## LIST OF SYMBOLS

$a$	speed of sound
$d$	shock tube diameter
$k$	turbulent kinetic energy
$M$	Mach number
$M_s$	shock Mach number
$p$	pressure
$p_p$	pitot pressure
$q$	dynamic pressure, normalized by $\rho V^2$
$T$	temperature
$t$	time
$u$	velocity component in $x$ direction
$u_s$	shock speed
$V$	total velocity
$w$	primary wavelength of periodic structure
$x$	distance along shock tube axis, measured from base, positive toward tube exit
$x_s$	axial distance from shock

### Greek Symbols

$\epsilon$	turbulent dissipation rate
$\delta$	boundary layer thickness
$\gamma$	ratio of specific heats, taken as 1.4
$\mu$	coefficient of viscosity
$\rho$	density
$\omega$	vorticity magnitude, normalized by $d/a_\infty$

### Subscripts

$j$	shock tube exit condition
$\infty$	free stream condition



INTENTIONALLY LEFT BLANK



NO. OF  
COPIES    ORGANIZATION

2    DEFENSE TECHNICAL INFO CTR  
      ATTN DTIC DDA  
      8725 JOHN J KINGMAN RD  
      STE 0944  
      FT BELVOIR VA 22060-6218

1    DIRECTOR  
      US ARMY RESEARCH LAB  
      ATTN AMSRL OP SD TA  
      2800 POWDER MILL RD  
      ADELPHI MD 20783-1145

1    DIRECTOR  
      US ARMY RESEARCH LAB  
      ATTN AMSRL OP SD TL  
      2800 POWDER MILL RD  
      ADELPHI MD 20783-1145

1    DIRECTOR  
      US ARMY RESEARCH LAB  
      ATTN AMSRL OP SD TP  
      2800 POWDER MILL RD  
      ADELPHI MD 20783-1145

ABERDEEN PROVING GROUND

5    DIR USARL  
      ATTN AMSRL OP AP L (305)



NO. OF  
COPIES    ORGANIZATION

- 13    COMMANDER  
US ARMY ARMAMENT RD&E CTR  
ATTN AMSTA AR AET A  
M AMORUSO  
E BROWN  
S CHUNG  
A FARINA  
J GRAU  
H HUDGINS  
W KOENIG  
C LIVECCHIA  
G MALEJKO  
C NG  
J THOMASOVICH  
W TOLEDO  
B WONG  
PICATINNY ARSENAL NJ 07806-5000
- 5    COMMANDER  
US ARMY ARMAMENT RD&E CTR  
ATTN AMSTA AR CCH B  
E FENNELL  
T LOUZEIRO  
D KITCHEN  
B KONRAD  
F QUEVEDO  
PICATINNY ARSENAL NJ 07806-5000
- 4    COMMANDER  
US ARMY ARMAMENT RD&E CTR  
ATTN AMSTA AR FSE  
E ANDRICOPOULIS  
K CHEUNG  
A GRAF  
D LADD  
PICATINNY ARSENAL NJ 07806-5000
- 6    COMMANDER  
US ARMY ARMAMENT RD&E CTR  
ATTN AMSTA AR CCL B  
D CONWAY  
D DAVIS  
K HAYES  
M PINCAY  
F PUZYCKI  
W SCHUPP  
PICATINNY ARSENAL NJ 07806-5000
- 1    COMMANDER  
US ARMY ARMAMENT RD&E CTR  
ATTN AMSTA AR CCH A  
J DIFUCCI  
PICATINNY ARSENAL NJ 07806-5000

NO. OF  
COPIES    ORGANIZATION

- 1    COMMANDER  
US ARMY MISSILE COMMAND  
ATTN AMSMI RD SS AT  
B WALKER  
REDSTONE ARSENAL AL 35898-5010
- 3    U.S. ARMY RESEARCH OFFICE  
ATTN G ANDERSON  
K CLARK  
T DOLIGOWSKI  
PO BOX 12211  
RESEARCH TRIANGLE PARK NC 27709-2211
- 2    DIRECTOR  
US ARMY BENET LABORATORY  
ATTN SMCAR CCB R  
P AALTO  
S SOPOK  
WATERVALIET NY 12189
- 1    DIRECTOR  
US BELVOIR RD&E CTR  
ATTN SATBE FED  
N BLACKWELL  
FORT BELVOIR VA 22060-5606
- 2    COMMANDER  
UNITED STATES MILITARY ACADEMY  
DEPARTMENT OF CIVIL  
AND MECHANICAL ENGINEERING  
ATTN M COSTELLO  
A DULL  
WEST POINT NY 10996
- 6    DIRECTOR  
NASA AMES RESEARCH CTR  
ATTN MS 258-1  
L SCHIFF  
T HOLST  
D CHAUSSEE  
T EDWARDS  
G MOLVIK  
S LAWRENCE  
MOFFETT FIELD CA 94035
- 1    DIRECTOR  
NASA AMES RESEARCH CTR  
ATTN MS 202-14 T HOLTZ  
MOFFETT FIELD CA 94035
- 1    DIRECTOR  
NASA AMES RESEARCH CTR  
ATTN MS 202A-1 M RAI  
MOFFETT FIELD CA 94035



NO. OF  
COPIES    ORGANIZATION

3    DIRECTOR  
NASA LANGLEY RESEARCH CTR  
ATTN TECHNICAL LIBRARY  
J SOUTH  
F WILCOX  
LANGLEY STATION  
HAMPTON VA 23665

3    COMMANDER  
AIR FORCE ARMAMENT LABORATORY  
ATTN AFATL/FXA  
G ABATE  
S ADELGREN  
B SIMPSON  
EGLIN AFB FL 32542-5434

2    COMMANDER  
US NAVAL SURFACE WARFARE CTR  
ATTN CODE R44  
A WARDLAW  
F PRIOLO  
WHITE OAK LABORATORY  
SILVER SPRING MD 20903-5000

2    COMMANDER  
US NAVAL SURFACE WARFARE CTR  
ATTN F MOORE  
T HYMES  
DAHLGREN VA 22448

2    COMMANDER  
USAF WRIGHT AERONAUTICAL LABS  
ATTN AFWAL/FIMG  
J SHANG  
WPAFB OH 45433-6553

1    COMMANDER  
ARNOLD ENG & DEV CTR  
CALSPAN FIELD SERVICE  
ATTN MS 600  
J BENEK  
AAFB TN 37389

2    DIRECTOR  
SANDIA NATIONAL LABS  
ATTN MS-1636  
W OBERKAMPF  
W WOLFE  
PO BOX 5800  
ALBUQUERQUE NM 87185-5800

NO. OF  
COPIES    ORGANIZATION

3    DIRECTOR  
SANDIA NATIONAL LABS  
ATTN MS-1511  
D BARNETTE  
F BLOTTNER  
M WALKER  
PO BOX 5800  
ALBUQUERQUE NM 87185-5800

5    DIRECTOR  
SANDIA NATIONAL LABS  
ATTN DOC CONTROL 3141  
C GHANBARI DIV 6215 MS 1127  
A CHABAI DIV 7112  
D GARDNER DIV 1421  
J MCGLAUN DIV 1541  
PO BOX 5800  
ALBUQUERQUE NM 87185-5800

1    DIRECTOR  
LOS ALAMOS NATIONAL LABORATORY  
ATTN MS C930  
B HOGAN  
LOS ALAMOS NM 87545

1    HQDA  
ATTN SARD TT  
F MILTON  
WASHINGTON DC 20310-0103

2    HQDA  
ATTN SARD TR  
K KOMINOS  
R CHAIT  
WASHINGTON DC 20310-0103

2    DIRECTOR  
FEDERAL EMERGENCY MNGMNT AGENCY  
ATTN PUBLIC RELATIONS OFFICE  
TECHNICAL LIBRARY  
WASHINGTON DC 20472

1    CHAIRMAN  
DOD EXPLOSIVES SAFETY BOARD  
BLDG 1 ROOM 856 C HOFFMAN  
2461 EISENHOWER AVENUE  
ALEXANDRIA VA 22331-0600

1    DIRECTOR OF DEFENSE RES  
AND ENGINEERING  
ATTN DD TWP  
WASHINGTON DC 20301



NO. OF  
COPIES    ORGANIZATION

- 1    DIRECTOR  
DEFENSE INTELLIGENCE AGENCY  
ATTN DT 2 WPNS & SYS DIVISION  
WASHINGTON DC 20301
  
- 1    ASSISTANT SECRETARY OF DEFENSE  
ATOMIC ENERGY  
ATTN DOCUMENT CONTROL  
WASHINGTON DC 20301
  
- 9    DIRECTOR  
DEFENSE NUCLEAR AGENCY  
ATTN CSTI TECHNICAL LIBRARY  
DDIR  
DFSP  
NANS  
OPNA  
SPSD  
SPTD  
DFTD  
TDTR  
WASHINGTON DC 20305
  
- 1    CHAIRMAN  
JOINT CHIEFS OF STAFF  
ATTN J5 R&D DIVISION  
WASHINGTON DC 20301
  
- 3    COMMANDER  
FIELD COMMAND DNA  
ATTN FCPR  
FCTMOF  
NMHE  
KIRTLAND AFB NM 87115
  
- 1    U S ARMY RESEARCH DEVELOPMENT  
AND STANDARDIZATION GROUP UK  
ATTN R REICHENBACH  
PSC 802 BOX 15  
FPO AE 09499-1500
  
- 10    CENTRAL INTELLIGENCE AGENCY  
DIR DB STANDARD  
ATTN GE 47 HQ  
WASHINGTON DC 20505
  
- 2    COMMANDER  
US ARMY NRDEC  
ATTN AMSNA D D SIELING  
STRNC UE J CALLIGEROS  
NATICK MA 01762

NO. OF  
COPIES    ORGANIZATION

- 1    DIRECTOR  
ADVANCED RESEARCH PROJECTS AGENCY  
ATTN TECHNICAL LIBRARY  
3701 NORTH FAIRFAX DRIVE  
ARLINGTON VA 22203-1714
  
- 2    COMMANDER  
US ARMY NRDEC  
ATTN SSCNC YSD J ROACH  
SSCNC WST A MURPHY  
KANSAS STREET  
NATICK MA 10760-5018
  
- 2    COMMANDER  
US ARMY CECOM  
ATTN AMSEL RD  
AMSEL RO TPPO P  
FT MONMOUTH NJ 07703-5301
  
- 1    COMMANDER  
US ARMY NGIC  
ATTN RESEARCH & DATA BRANCH  
220 7TH STREET NE  
CHARLOTTESVILLE VA 22901-5396
  
- 1    US ARMY MISSILE & SPACE  
INTELLIGENCE CENTER  
ATTN AIAMS YDL  
REDSTONE ARSENAL AL 35898-5500
  
- 1    COMMANDING OFFICER CODE L51  
NAVAL CIVIL ENGINEERING LAB  
ATTN J TANCRETO  
PORT HUENEME CA 93043-5003
  
- 3    COMMANDER  
US ARMY CORPS OF ENGINEERS  
WATERWAYS EXPERIMENT STATION  
ATTN CEWES SS R J WATT  
CEWES SE R J INGRAM  
CEWES TL TECH LIBRARY  
PO BOX 631  
VICKSBURG MS 39180-0631
  
- 2    COMMANDER  
US ARMY STRATEGIC DEFENSE COMMAND  
ATTN CSSD H MPL TECH LIB  
CSSD H X DAVIES  
PO BOX 1500  
HUNTSVILLE AL 35807



NO. OF  
COPIES    ORGANIZATION

1    COMMANDER  
US ARMY ENGINEER DIVISION  
ATTN HNDED FD  
PO BOX 1500  
HUNTSVILLE AL 35807

3    COMMANDER  
US ARMY NUCLEAR & CHEMICAL AGENCY  
7150 HELLER LOOP SUITE 101  
SPRINGFIELD VA 22150-3198

1    COMMANDER  
US ARMY CORPS OF ENGINEERS  
FT WORTH DISTRICT  
ATTN CESWF PM J  
PO BOX 17300  
FT WORTH TEXAS 76102-0300

1    DIRECTOR  
TRAC FLVN  
ATTN ATRC  
FT LEAVENWORTH KS 66027-5200

1    COMMANDER  
US ARMY RESEARCH OFFICE  
ATTN SLCRO D  
PO BOX 12211  
RESEARCH TRIANGLE PARK NC 27709-2211

1    DIRECTOR  
HQ TRAC RPD  
ATTN ATRC RPR RADD  
FT MONROE VA 23651-5143

2    OFFICE OF NAVAL RESEARCH  
ATTN A FAULSTICK CODE 23  
800 N QUINCY STREET  
ARLINGTON VA 22217

1    DIRECTOR  
TRAC WSMR  
ATTN ATRC WC KIRBY  
WSMR NM 88002-5502

1    COMMANDER  
NAVAL SEA SYSTEMS COMMAND  
ATTN CODE SEA 62R  
DEPARTMENT OF THE NAVY  
WASHINGTON DC 20362-5101

1    COMMANDER  
US ARMY WSMR  
ATTN STEWS NED MEASON  
WSMR NM 88002-5158

NO. OF  
COPIES    ORGANIZATION

1    COMMANDER  
DAVID TAYLOR RESEARCH CENTER  
ATTN CODE 522 TECH INFO CTR  
BETHESDA MD 20084-5000

1    OFFICER IN CHARGE CODE L31  
CIVIL ENGINEERING LABORATORY  
NAVAL CONSTRUCTION BATTALION CTR  
ATTN TECHNICAL LIBRARY  
PORT HUENEME CA 93041

1    COMMANDING OFFICER  
WHITE OAK WARFARE CENTER  
ATTN CODE WA501 NNPO  
SILVER SPRING MD 20902-5000

1    COMMANDER CODE 533  
NAVAL WEAPONS CENTER  
ATTN TECHNICAL LIBRARY  
CHINA LAKE CA 93555-6001

1    COMMANDER  
DAHLGREN DIVISION  
NAVAL SURFACE WARFARE CENTER  
ATTN CODE E23 LIBRARY  
DAHLGREN VA 22448-5000

1    COMMANDER  
NAVAL RESEARCH LABORATORY  
ATTN CODE 2027 TECHNICAL LIBRARY  
WASHINGTON DC 20375

1    OFFICER IN CHARGE  
WHITE OAK WARFARE CTR DETACHMENT  
ATTN CODE E232 TECHNICAL LIBRARY  
10901 NEW HAMPSHIRE AVENUE  
SILVER SPRING MD 20903-5000

1    AL LSCF  
ATTN J LEVINE  
EDWARDS AFB CA 93523-5000

1    COMMANDER  
NAVAL WEAPONS EVALUATION FAC  
ATTN DOCUMENT CONTROL  
KIRTLAND AFB NM 87117

1    RADC EMTLD DOCUMENT LIBRARY  
GRIFFISS AFB NY 13441

1    AEDC  
ATTN R MCAMIS  
MAIL STOP 980  
ARNOLD AFB TN 37389



NO. OF  
COPIES    ORGANIZATION

- 1    OLAC PL TSTL  
      ATTN D SHIPLETT  
      EDWARDS AFB CA 93523-5000
- 1    AFIT ENY  
      ATTN LTC HASEN  
      WRIGHT PATTERSON AFB OH 45433-6583
- 1    AFIT  
      ATTN TECHNICAL LIBRARY  
      BLDG 640 B  
      WRIGHT PATTERSON AFB OH 45433
- 2    AIR FORCE ARMAMENT LABORATORY  
      ATTN AFATL DOIL  
      AFATL DLYV  
      EGLIN AFB FL 32542-5000
- 1    DIRECTOR  
      LAWRENCE LIVERMORE NATIONAL LAB  
      ATTN TECH INFO DEPT L 3  
      PO BOX 808  
      LIVERMORE CA 94550
- 1    DIRECTOR  
      NATIONAL AERONAUTICS & SPACE ADMIN  
      ATTN SCIENTIFIC & TECH INFO FAC  
      PO BOX 8757 BWI AIRPORT  
      BALTIMORE MD 21240
- 1    FTD NIIS  
      WRIGHT PATTERSON AFB OH 45433
- 1    DIRECTOR  
      IDAHO NATIONAL ENGINEERING LAB  
      ATTN SPEC PROGRAMS J PATTON  
      2151 NORTH BLVD MS 2802  
      IDAHO FALLS ID 83415
- 4    DIRECTOR  
      IDAHO NATIONAL ENGINEERING LAB  
      EG&G IDAHO INC  
      ATTN R GUENZLER MS 3505  
      R HOLMAN MS 3510  
      R BERRY  
      W REED  
      PO BOX 1625  
      IDAHO FALLS ID 83415
- 3    INST FOR ADVANCED TECHNOLOGY  
      UNIV OF TEXAS AT AUSTIN  
      ATTN W REINECKE  
      T KIEHNE  
      D BARNETT  
      4030-2 W BRAKER LANE  
      AUSTIN TX 78759-5329

NO. OF  
COPIES    ORGANIZATION

- 2    UNIV OF CALIFORNIA DAVIS  
      DPT OF MECHANICAL ENGINEERING  
      ATTN H DWYER  
      B MEAKIN  
      DAVIS CA 95616
- 1    UNIVERSITY OF MARYLAND  
      DPT OF AEROSPACE ENGINEERING  
      ATTN J ANDERSON JR  
      COLLEGE PARK MD 20742
- 1    UNIVERSITY OF TEXAS  
      DPT OF AEROSPACE ENGINEERING  
      AND ENGINEERING MECHANICS  
      ATTN D DOLLING  
      AUSTIN TEXAS 78712-1055
- 1    UNIVERSITY OF DELAWARE  
      DPT OF MECHANICAL ENGINEERING  
      ATTN L SCHWARTZ  
      NEWARK DE 19716
- 4    UNIVERSITY OF CINCINNATI  
      DPT OF AEROSPACE ENGINEERING  
      ATTN K GHIA  
      P KHOSLA  
      S RUBIN  
      G SLATER  
      MAIL LOCATION 70  
      CINCINNATI OH 45221
- 1    UNIVERSITY OF FLORIDA  
      DPT OF ENGINEERING SCIENCES  
      ATTN C HSU  
      GAINESVILLE FL 32611
- 2    UNIV OF ILLINOIS URBANA CHAMPAIGN  
      DPT OF MECHANICAL AND  
      INDUSTRIAL ENGINEERING  
      ATTN A ADDY  
      C DUTTON  
      114 MECHANICAL ENGINEERING BUILDING  
      1206 WEST GREEN ST.  
      URBANA IL 61801
- 3    PENNSYLVANIA STATE UNIVERSITY  
      DPT OF MECHANICAL ENGINEERING  
      ATTN K KUO  
      C MERKLE  
      G SETTLES  
      UNIVERSITY PARK PA 16802



NO. OF  
COPIES    ORGANIZATION

1 FLORIDA ATLANTIC UNIVERSITY  
DPT OF MECHANICAL ENGINEERING  
ATTN W CHOW  
BOCA RATON FL 33431

1 NORTH CAROLINA STATE UNIVERSITY  
DPT OF MECHANICAL AND  
AEROSPACE ENGINEERING  
ATTN D MCCRAE  
BOX 7910  
RALEIGH NC 27695-7910

1 UNIVERSITY OF MINNESOTA  
ARMY HIGH PERF COMP RES CTR  
ATTN T TEZDUYAR  
1100 WASHINGTON AVE SOUTH  
MINNEAPOLIS MN 55415

1 MIT  
ATTN TECHNICAL LIBRARY  
CAMBRIDGE MA 02139

1 STATE UNIVERSITY OF NEW YORK  
MECHANICAL & AEROSPACE ENGINEERING  
ATTN P GIVI  
BUFFALO NY 14260

2 UNIVERSITY OF MARYLAND  
INSTITUTE FOR ADV COMPUTER STUDIES  
ATTN L DAVIS  
G SOBIESKI  
COLLEGE PARK MD 20742

1 NORTHROP UNIVERSITY  
ATTN F SAFFORD  
5800 W ARBOR VITAE STREET  
LOS ANGELES CA 90045

1 CALIFORNIA INSTITUTE OF TECHNOLOGY  
ATTN T AHRENS  
1201 E CALIFORNIA BLVD  
PASADENA CA 91109

2 MDA ENGINEERING INC  
ATTN J STEINBRENNER  
D ANDERSON  
500 E BORDER ST SUITE 401  
ARLINGTON TX 76010

2 PHYSICS INTERNATIONAL CORP  
PO BOX 5010  
SAN LEANDRO CA 94577-0599

NO. OF  
COPIES    ORGANIZATION

2 FC DNA  
ATTN DASIAAC BLDG 20676  
1680 TEXAS ST SE  
KIRTLAND AFB NM 87117-5669

1 R&D ASSOCIATES  
ATTN G GANONG  
PO BOX 9377  
ALBUQUERQUE NM 87119

3 ALLIANT TECHSYSTEMS INC  
ATTN M SWENSON  
S BECKER  
S BURRETTA  
MAIL STATION MN48-3700  
7225 NORTHLAND DR  
BROOKLYN PARK MN 55428

1 ALLIANT TECHSYSTEMS INC  
ATTN ROGER A RAUSCH  
600 2ND STREET NE  
HOPKINS MN 55343-8367

1 CARPENTER RESEARCH CORP  
ATTN H CARPENTER  
27520 HAWTHORNE BLVD SUITE 263  
PO BOX 2490  
ROLLING HILLS ESTATES CA 90274

1 AEROSPACE CORPORATION  
ATTN TECH INFO SERVICES  
PO BOX 92957  
LOS ANGELES CA 90009

1 THE BOEING COMPANY  
ATTN AEROSPACE LIBRARY  
PO BOX 3707  
SEATTLE WA 98124

2 FMC CORPORATION  
ADVANCED SYSTEMS CENTER  
ATTN J DROTLEFF  
C KREBS MDP 95  
BOX 58123  
2890 DE LA CRUZ BLVD  
SANTA CLARA CA 95052

1 SVERDRUP TECHNOLOGY INC  
SVERDRUP CORPORATION AEDC  
ATTN B HEIKKINEN  
MS 900  
ARNOLD AFB TN 37389-9998



NO. OF  
COPIES    ORGANIZATION

- 1    KTECH CORPORATION  
      ATTN E GAFFNEY  
      901 PENNSYLVANIA AVE NE  
      ALBUQUERQUE NM 87111
- 1    EATON CORPORATION  
      DEFENSE VALVE & ACTUATOR DIV  
      ATTN J WADA  
      2338 ALASKA AVE  
      EL SEGUNDO CA 90245-4896
- 2    MCDONNELL DOUGLAS  
      ASTRONAUTICS CORP  
      ATTN R HALPRIN  
      KA HEINLY  
      5301 BOLSA AVENUE  
      HUNTINGTON BEACH CA 92647
- 4    KAMAN AVIDYNE  
      ATTN R RUETENIK 2 CP  
      S CRISCIONE  
      R MILLIGAN  
      83 SECOND AVENUE  
      NORTHWEST INDUSTRIAL PARK  
      BURLINGTON MA 01830
- 1    GENERAL RESEARCH CORP  
      ATTN H KING  
      PO BOX 6770  
      SANTA BARBARA CA 93160-6770
- 7    KAMAN SCIENCES CORP  
      ATTN PA ELLIS  
      J FORKOIS  
      T HAYDEN  
      W LEONARD  
      R PROZAN  
      F SHELTON  
      E STATTON  
      1500 GARDEN OF THE GODS RD.  
      COLORADO SPRINGS CO 80907
- 4    HERCULES INC  
      ALLEGANY BALLISTICS LABORATORY  
      ATTN J CONDON  
      W NYGA  
      J PARRILL  
      J VILES  
      PO BOX 210  
      ROCKET CTR WV 26726

NO. OF  
COPIES    ORGANIZATION

- 1    FORD MOTOR COMPANY  
      ATTN T GIELDA  
      15031 S COMMERCE DR  
      SUITE 100  
      DEARBORN MI 48120
- 2    VRA INC.  
      ATTN C LEWIS  
      B BHUTTA  
      PO BOX 50  
      BLACKSBURG VA 24060
- 1    BLACK & VEATCH ENGINEERS  
      ARCHITECTS  
      ATTN H LAVERENTZ  
      1500 MEADOW LAKE PARKWAY  
      KANSAS CITY MO 64114
- 2    APPLIED RESEARCH ASSOCIATES INC  
      ATTN J KEEFER  
      N ETHRIDGE  
      PO BOX 548  
      ABERDEEN MD 21001
- 1    ADA TECHNOLOGIES INC  
      ATTN J BUTZ  
      HONEYWELL CENTER SUITE 110  
      304 INVERNESS WAY SOUTH  
      ENGLEWOOD CO 80112
- 1    MEDICOMP TECHNOLOGIES INC.  
      ATTN S CHAKRAVARTHY  
      5540 WEMBLY AVE.  
      AGOURA CA 91301
- 2    SCIENCE CENTER  
      ROCKWELL INTERNATIONAL CORP  
      ATTN S RAMAKRISHNAN  
      D OTA  
      1049 CAMINO DOS RIOS  
      THOUSAND OAKS CA 91360
- 1    ORLANDO TECHNOLOGY INC  
      ATTN D MATUSKA  
      60 SECOND STREET BLDG 5  
      SHALIMAR FL 32579
- 2    THE RALPH M PARSONS COMPANY  
      ATTN T JACKSON  
      LB TS PROJECT MANAGER  
      100 WEST WALNUT STREET  
      PASADENA CA 91124



NO. OF  
COPIES    ORGANIZATION

1 SAIC  
ATTN J GUEST  
2301 YALE BLVD SE SUITE E  
ALBUQUERQUE NM 87106

1 SAIC  
ATTN N SINHA  
501 OFFICE CENTER DR APT 420  
FT WASHINGTON PA 19034-3211

1 SUNBURST RECOVERY INC  
ATTN C YOUNG  
PO BOX 2129  
STEAMBOAT SPRINGS CO 80477

1 SVERDRUP TECHNOLOGY INC  
ATTN R STARR  
PO BOX 884  
TULLAHOMA TN 37388

3 S CUBED  
A DIVISION OF MAXWELL LABS INC  
ATTN TECHNICAL LIBRARY  
R DUFF  
K PYATT  
PO BOX 1620  
LA JOLLA CA 92037-1620

2 S CUBED  
A DIVISION OF MAXWELL LABS INC  
ATTN C NEEDHAM  
L KENNEDY  
2501 YALE BLVD SE  
ALBUQUERQUE NM 87106

3 SRI INTERNATIONAL  
ATTN GR ABRAHAMSON  
J GRAN  
DR B HOLMES  
333 RAVENWOOD AVENUE  
MENLO PARK CA 94025

1 TRW  
BALLISTIC MISSILE DIVISION  
ATTN H KORMAN  
MAIL STATION 526 614  
PO BOX 1310  
SAN BERNADINO CA 92402

1 BATTELLE  
TWSTIAC  
505 KING AVENUE  
COLUMBUS OH 43201-2693

NO. OF  
COPIES    ORGANIZATION

1 THERMAL SCIENCE INC  
ATTN R FELDMAN  
2200 CASSENS DRIVE  
ST LOUIS MO 63026

2 DENVER RESEARCH INSTITUTE  
ATTN J WISOTSKI  
TECHNICAL LIBRARY  
PO BOX 10758  
DENVER CO 80210

3 SOUTHWEST RESEARCH INSTITUTE  
ATTN DR C ANDERSON  
S MULLIN  
A B WENZEL  
PO DRAWER 28255  
SAN ANTONIO TX 78228-0255

ABERDEEN PROVING GROUND

1 CDR USATECOM  
ATTN AMSTE TE F L TELETSKI

1 CDR USATHAMA  
ATTN AMSTH TE

1 CDR USATC  
ATTN STEC LI

5 COMMANDER  
US ARMY ARMAMENT RD&E CTR  
ATTN AMSTA AR FSF T  
R LIESKE  
J MATTS  
F MIRABELLE  
R PUHALLA  
J WHITESIDE

64 DIRECTOR  
US ARMY RESEARCH LABORATORY  
ATTN AMSRL SC C NIETUBICZ  
AMSRL SC CC  
R ANGELINI  
P COLLINS  
C ELLIS  
J GROSH  
D HISLEY  
R SHEROKE  
AMSRL SC I W STUREK  
AMSRL SC S R PEARSON  
AMSRL SL CM E FIORVANTE  
AMSRL WT N J INGRAM  
AMSRL WT NA R KEHS



NO. OF  
COPIES    ORGANIZATION

AMSRL WT NC  
R LOTTERO  
R LOUCKS  
A MIHALCIN  
P MULLER  
S SCHRAML  
AMSRL WT ND J MILETTA  
AMSRL WT NF L JASPER  
AMSRL WT NG T OLDHAM  
AMSRL WT NH J CORRIGAN  
AMSRL WT P  
A HORST  
E SCHMIDT  
AMSRL WT PA  
P CONROY  
G KELLER  
D KRUCZYNSKI  
T MINOR  
M NUSCA  
AMSRL WT PB  
M BUNDY  
G COOPER  
H EDGE  
K FANSLER  
E FERRY  
J GARNER  
B GUIDOS  
K HEAVEY  
D LYON  
A MIKHAIL  
V OSKAY  
P PLOSTINS  
J SAHU  
K SOENCKSEN  
P WEINACHT  
AMSRL WT PC  
G ADAMS  
R FIFER  
AMSRL WT PD  
B BURNS  
W DRYSDALE  
G GAZONAS  
D HOPKINS  
R LIEB  
S WILKERSON  
AMSRL WT TA W GILLICH  
AMSRL WT TB W DEROSSET  
AMSRL WT TC A DIETRICH  
AMSRL WT TD R FREY  
AMSRL WT W  
C MURPHY

NO. OF  
COPIES    ORGANIZATION

AMSRL WT WB  
F BRANDON  
T BROWN  
L BURKE  
W D'AMICO  
B DAVIS  
D HEPNER  
M HOLLIS  
AMSRL WT WC  
R VON WAHLDE  
AMSRL WT WD  
T KOTTKE  
C STUMPFEL